



SANITIZED® COLORFILLER / GROUT CURE

SANDED & UNSANDED 2 PART WATERPROOF TILE & PEBBLE GROUT



ECO FRIENDLY



WATER BASED



EASE OF USE

DESCRIPTION

A two-part waterproofed cement-based colorgrout which is stain, water and chemical resistant and resistance to a broad spectrum of fungal, algae and bacteriological degradation.

USES

Available in wide range of colours to fill joints between tiles and stones.

For joints between 1-6mm for unsanded, 6-10mm for sanded.

Used in intended hygienic conditions such as hospitals, kitchens, food preparation areas.

Used in wet areas like swimming pools and spas.

Used in general applications of superior performance, eg. external walkways and trafficable areas.

Can be used in place of specifications requiring the use of epoxy grouts for rapid installations.

For decorative pebble wash areas with low maintenance and easy care

ADVANTAGES

- A non-shrink coloured filler different from ordinary pigmented cements.
- Pigments within the grout are evenly and totally dispersed.
- Colourfast and ultra-violet (U.V) resistant.
- Reduces water absorption through tile joints.
- Improve stain and oil resistant.

TECHNICAL DATA

Properties	Results (Unsanded)	Results (Sanded)
Form	2-Component Powder & Liquid	2-Component Powder & Liquid
Compressive Strength @28 days [BSEN 12808-3:2002]	34.7N/mm ²	16.8N/mm ²
Resistance to Abrasion [BSEN 12808-2:2002]	1163mm ³	375mm ³
Flexural Strength at 28 days [BSEN 12808-3:2002]	10.9N/mm ²	9.7N/mm ²
Water Absorption (g) @ 30 mins [BSEN 12808-5:2002]	0.7	0.4
@ 240 mins [BSEN 12808-5:2002]	1.8	0.7
Shrinkage @ 28 days [BSEN 12808-4:2002]	0.4	0.2
Colour Fastness	Passed	Passed

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

PREPARATION OF TILE SURFACE BEFORE GROUTING

Depending on the type of adhesive used for tiling, grouting shall commence the next day after the adhesive has set but within 7 days upon completion of tiling.

When using Davco Rapidbond 2-Part rapid setting adhesive, grouting may commence immediately after the adhesive has set.

Ensure that all tile joints are clean and free from dust and debris, removal means include air blowing or vacuum.





SANITIZED® COLORFILLER / GROUT CURE

MIXING & APPLICATION

Mixing ratio (Powder to liquid)

Unsanded 1 : 0.28 (kg)
Sanded 1 : 0.19 (kg)

Pour the Liquid component into the clean mixing bucket. While stirring, gradually add the Powder component, stirring continuously until a lump-free, toothpaste consistency is achieved. Allow the mixed material to stand for 10 minutes, restir before use.

Using a rubber float or squeegee to work the grout into the joints in a diagonal motion making sure that the grout is deep in the joints and does not sit on top the joints ie. the grout does not bridge the joint.

Remove excess grout from the surface of the tiles with the rubber float or squeegee using a diagonal motion to avoid dislodging the embedded grout.

It is advisable to grout only 2 to 4 square metres at a time before commencing clean up, or preferably use a two-man team. This way, one grouts and the other cleans up, reducing the chance of the grout drying on the tiles.

Use a damp sponge to clean up the remainder of the grout. Regularly rinsing the sponge out to assist in cleaning. For best result, use warm water when cleaning.

In the cleaning process, do not flood the floor with water and ensure that the sponge is kept clean and the water is changed regularly.

After the grout has dried, the tiled surface shall be cleaned with damp cloth followed by a clean dry cloth to give it a final polish.

When using Davco Sanitized® Colorfiller / Grout Cure, for decorative pebble wash area, it is recommended to coat with Lanko Tufseal, an acrylic non yellowing, clear protective coating, for ease of cleaning and low maintenance.

With anti-slip or textured tiles, it is advisable to pre-test the method of clean-off, before attempting to grout the entire tiled area.

Allow the grout to cure for 48 hours before exposing to the intended environment.

CLEANING

Tools and equipment must be cleaned up in water before the grout dries thoroughly. Use Davco Tile and Grout Cleaner if the grout has dried prior to clean up.

SHELF LIFE

Shelf life of up to 12 months in unopened containers when stored in a cool dry elevated place.

PACKAGING

Unsanded = 32.5 kg / set
Sanded = 30 kg / set

HEALTH & SAFETY

This product is non-toxic. In case of excessive skin contact, flush with plenty of water. If ill effects should occur, seek medical attention immediately. Refer to safety data sheet.

Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website www.parexgroup.com.sg



Mixing



Using rubber float or squeegee



Float the grout material



Clean with damp sponge / cloth

PAREXGROUP PTE LTD

28 TUAS SOUTH AVENUE 8, SINGAPORE 637648

TEL: (65) 6861 0632 FAX: (65) 6862 3915

EMAIL: SALES@PAREXGROUP.COM.SG

WEBSITE: WWW.PAREXGROUP.COM.SG



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



ISO 14004 : 2006
Certificate No. M-SYS / GHG / 8802



ParexGroup, a French multi-national company with headquarters in Paris, is a leading manufacturer of speciality products for the construction industry with operations in more than 20 countries, and our 2700 people around the world are the cornerstone of our growing organization.

Updated TA30 Oct 2015